


HFP-8022-42-ER16

Technische Daten | Technical data

Typenbezeichnung Type designation	mechatron HFP-8022-42-ER16	Kühlart Cooling method	Flüssigkeitskühlung Liquid cooling
Leistung Power	S1 (100%) 2,2 kW S6 (50%) 2,5 kW	Kühlmitteltemperatur Coolant temperature	max. 35 °C
Drehzahl Speed	42.000 U/min	Thermoschutz Thermal protection	Bimetallschalter (Öffner) Bimetal switch (NC contact)
Spannung Voltage	230 V	Schutzart IP Code	IP54
Strom Current	S1 (100%) 8,0 A S6 (50%) 10,0 A	Spindellager Spindle bearings	Hochpräzisionslager wartungsfrei gemäß Standard ABEC7/P4S High precision bearings mainten. free according to ABEC7/P4S
Frequenz Frequency	700 Hz	Rundlauf (Kegel) Runout (taper)	< 2,0 µm
Eckfrequenz Base frequency	400 Hz	Werkzeugwechsel Tool change	Manuell, Spannmutter Manually, clamping nut
Polzahl Number of poles	2	Werkzeugschnittstelle Tool interface	ER16
Pneumatikanschlüsse Pneumatic connections	Sperrluft Sealing air	Spannbereich Clamping Range	1 - 10 mm
Gewicht Weight	4,8 kg		

Motorkennlinie | Motor characteristic



Abmessungen | Dimensions

